

# ICONIX

## The World's Smallest HD Video Camera Remote Control RCP-160

### General Specifications

- Control of up to six cameras from a single RCP
- Touch-screen LCD Graphic-User Interface for full menu and control access
- Dedicated and assignable encoder knobs
- Lens motor control, including Zoom, Focus and Iris
- Dedicated and user-definable buttons
- Full camera paint and feature control
- Upload capability of scene files to cameras
- 3 in 1 Memory card interface for scene and setup storage

### Front Panel

- LCD touch panel
- 3.5" 320 x 240-pixel (1/4-VGA) LCD display
- Touchscreen interface for menu navigation and control
- GUI capable of accessing/controlling all camera operational parameters
- GUI Assist Controls
- 4 assignable encoder knobs for parameter adjustment
- 6 dedicated buttons for quick navigation to major menus

### Memory Stick Interface

- Slot accepts Sony Memory Stick, SD Card, and other media devices for file storage
- Push-in-push-out style ejection mechanism
- LED lamp for access indication

### Performance

- Power input: 12V nominal, range TBD
- Power consumption: TBD
- Ambient Temperature: 0C to 40C (target)
- Ambient humidity: <80% (target)

### Product Details

- Dimensions: 14.0" x 4.125" x 2.8"

### Connector Panel

- One XLR-4 Male: 12V DC power input
- Six male DSUB-9 connectors for RS-232 camera control, configured as DTE
- One female DSUB-9 connector for external I/O, configured as RS-232 DCE

